



FIELDKING MOUNTED DISC PLOUGH



BENEFITS :

- The disc plough is designed to work in all types of soil for basic functions such as soil breaking, soil raising, soil turning and soil mixing.
- It is used to open the new fields and to process the stony areas.
- It can be used easily at rocky and rooted areas.
- It is especially useful in hard and dry trashy land conditions and in soils where scouring is a major problem.

FEATURES :

- In conformity with the soil conditions it is being produced with 2-3-and 4 bottoms version with an option for extra kit for converting it to extra-bottom plough.
- It is directly mounted to the tractors.
- Extra heavy-duty pipe frame has high trash clearance allowing the plough to operate under heavy crop residue.

SPECIFICATIONS :

CODE	MDP-001A	MDP-001B	MDP-001C	MDP-001E
SIZE	2 BOTTOM	3 BOTTOM	4 BOTTOM	5 BOTTOM (4+1)
FRAME	Extra Heavy Duty Tubular Frame (OD 168 mm, ID 146 mm)	Extra Heavy Duty Tubular Frame (OD 168 mm, ID 146 mm)	Extra Heavy Duty Tubular Frame (OD 168 mm, ID 146 mm)	Extra Heavy Duty Tubular Frame (OD 168 mm, ID 146 mm)
MOUNTED	CAT – II	CAT – II	CAT – II	CAT – II
LENGTH	1800 mm	2400 mm	3000 mm	3600 mm
WIDTH	820 mm	1040 mm	1260 mm	1480 mm
HEIGHT	1220 mm	1220 mm	1220 mm	1220 mm
DISCS	660 x 6 mm	660 x 6 mm	660 x 6 mm	660 x 6 mm
DISC SPACING	570mm	570mm	570mm	570mm
COLTER DISC	500 x 6 mm	500 x 6 mm	500 x 6 mm	500 x 6 mm
SCRAPPER	6 mm – adjustable	6 mm – adjustable	6 mm – adjustable	6 mm – adjustable
BEARINGS	2 Nos. Taper Roller/disc	2 Nos. Taper Roller/disc	2 Nos. Taper Roller/disc	2 Nos. Taper Roller/disc
WIDTH OF CUT	500 – 550 mm	875 – 925 mm	1150 – 1200 mm	1575 – 1625 mm
WEIGHT	295 Kg (approx)	395 Kg (approx)	495 Kg (approx)	610 Kg (approx)
TRACTOR (HP)	45-50	60-65	75-85	100-110

*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Mfg. By:

BERI UDYOG PVT. LTD.

(AN ISO 9001-2000 COMPANY)

PLOT NO.100-101, SECTOR 3, HSIIDC, KARNAL (HARYANA) INDIA

PH: 00 91 184 2221571/72/73, FAX: 00 91 184 2221574

E-mail: info@fieldking.com, Homepage: www.fieldking.com