



## FIELDKING ROTARY SLASHER (LAWN MOWER)



### Rotary Slasher / Stub-Cutter / Grass-Cutter (Lawn Mower)

The Grass Cutter Mower Horizontal slashing is the most versatile method of grass cutting. Rotary slasher is powerful enough to cope with tall weeds and small bushes, yet giving a satisfactory fine cut on turf areas mounted with optional front and rear rollers, scalping is minimal. Tractor-mounted rotary slasher, grass slasher provide a very cost-effective grass cutting solution. FIELDKING rotary slasher is one of the best machines in itself for cutting unwanted wild grass.

#### FEATURES :

1. Designed for fast application to any type of 50-80 HP tractor with three point linkage.
2. Safety chain shield standard.
3. Tractor Driven suitable for P.T.O. 540 r.p.m.
4. Rotary slasher and grass slasher having reversible steel blades for cutting wild grass, shrubs, weeds, sugar cane stacks, etc.
5. Cutting width: approx. 6 feet OR 8 feet
6. Height adjustment: 1" –8"

#### SPECIFICATIONS :

| S.N. | DESCRIPTION         | 6'                      | 8'                      |
|------|---------------------|-------------------------|-------------------------|
| 1    | GEAR BOX            | Single Speed 540 r.p.m. | Single Speed 540 r.p.m. |
| 2    | SHEET               | 10 Gauge                | 10 Gauge                |
| 3    | MAIN FRAME          | 50X6 Angle              | 65X6 Angle              |
| 4    | THREE POINT LINKAGE | 50X16 FLAT              | 50X16 FLAT              |
| 5    | WHEEL               | 1                       | 2                       |
| 6    | DEPTH CONTROL       | 1"-8"                   | 1"-8"                   |
| 7    | TYRE DIA            | 12"                     | 12"                     |
| 8    | BLADE               | Boron Steel             | Boron Steel             |
| 9    | P.T.O.              | With shear bolt         | With shear bolt         |
| 10   | LENTH               | 1905 mm                 | 2514 mm                 |
| 11   | WIDTH               | 1828 mm                 | 2438 mm                 |
| 12   | CUTTING WIDTH       | 1750 mm                 | 2360 mm                 |
| 13   | WEIGHT              | 328 Kgs. (Approx.)      | 412 Kgs. (Approx.)      |

\*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Mfg. By:

**BERI UDYOG PVT. LTD.**

(AN ISO 9001-2000 COMPANY)

PLOT NO.100-101, SECTOR 3, HSIIDC, KARNAL (HARYANA) INDIA

PH: 00 91 184 2221571/72/73, FAX: 00 91 184 2221574

E-mail: [info@fieldking.com](mailto:info@fieldking.com), Homepage: [www.fieldking.com](http://www.fieldking.com)