



## FIELDKING TYNE RIDGER



### **BENEFITS :**

1. Depth of the ridger could be adjusted with the side tyres.
2. It is mostly used for sugarcane plantation.

### **FEATURES :**

1. It has heavy duty box type frame.
2. It can produce ridge with maximum width of 900 mm.

### **SPECIFICATIONS :**

<b>NO. OF FURROWS</b>	3 Furrow	4 Furrow
<b>FRAME ( mm)</b>	Heavy duty box frame 100x8	Heavy duty box frame 100x8
<b>MAST HEIGHT</b>	21”	21”
<b>OVERALL LENGTH (mm)</b>	2768	3683
<b>MOUNTING</b>	CAT – I / II	CAT – I / II
<b>FASTENERS</b>	High Tensile	High Tensile
<b>TYPE OF TYRE</b>	600 –16	600 –16
<b>POWER REQUIRED (HP)</b>	60	70
<b>WEIGHT (kg) (approx )</b>	330	400

\*The weight and working data contained in the present leaflet are supplied for information only and are not binding. Specification and size can be altered as part of ongoing product modification/improvement.

Mfg. By:

**BERI UDYOG PVT. LTD.**

(AN ISO 9001-2000 COMPANY)

PLOT NO.100-101, SECTOR 3, HSIIDC, KARNAL (HARYANA ) INDIA

PH: 00 91 184 2221571/72/73, FAX: 00 91 184 2221574

E-mail: [info@fieldking.com](mailto:info@fieldking.com), Homepage: [www.fieldking.com](http://www.fieldking.com)